

New Dimensions Solutions, LLC

# ND GRAFFITI SHIELD™

Water Based Sealer/Finish

**Tough - Durable Finish**  
**FOR THE GRAFFITI SHIELD SYSTEM**  
**Protects Painted, Unpainted, Porous**  
**Surfaces From Graffiti Damage and Fading**

**PROTECTION YOU CAN COUNT ON!**

**VERY MILD ODOR**

**LOW VOC - Only 16.2 g/l per California VOC Regulations**

**Easy To Use - Fast Drying - Low Use Cost**

**Does Not Yellow, Crack, Peel, Flake or Chip**

**Stops Sun, Water and Most Chemical Damage**

**High Spread Rates (500 - 1000+ sq.ft. for 4 coats)**

**CAUTION:**

**MAY BE SKIN AND EYE IRRITANT**

**Read All Cautions On Side Panel**

**Before Using This Product**

**KEEP OUT OF REACH OF CHILDREN!**

**NET CONTENT**

Quart (0.946 liter)     Gallon (3.784 liters)     5 Gallon (18.92 liters)

## APPLICATION DIRECTIONS:

The substrate must be first primed with ONE COAT™ in sufficient quantity so that it is visible and can be felt on the surface. After it is dry to the touch apply ND GRAFFITI SHIELD™ by spray (airless sprayer with 0.015 or 0.013 tip at about 300-500 PSI is recommended for most large painted and all porous surfaces; low pressure hand pump sprayer at about 35 PSI could be used on very porous surfaces), mop or brush. The application should be thin and ND GRAFFITI SHIELD™ should appear water clear when applied. On semi-porous materials use a quality sponge mop to spread in any runs.

THE GRAFFITI SHIELD SYSTEM™ is a total of 4 separate coats of ND GRAFFITI SHIELD™ over the base application of ONE COAT™. Each coat must be dry to the touch before next coat is applied. Drying time may vary between few minutes to an hour depending upon the weather, humidity and ventilation. THE GRAFFITI SHIELD SYSTEM™ should be used after 96 hours which is the cure time. Should cleaning be necessary before 96 hours, reapply ND GRAFFITI SHIELD™ to the needed areas only. Do not allow this product to freeze and do not use it in freezing temperatures. However, once it is applied and cured, freeze/thaw cycles will have no effect on proper product performance.

Remove new graffiti from THE GRAFFITI SHIELD SYSTEM™ in 24 hours or less for better results. Use only DISAPPEAR Organic Graffiti/Adhesive Remover™ with a soft cloth, sponge or soft bristled brush. Rinse with water and check appearance. When necessary, touch up cleaned areas with a light coat of ND GRAFFITI SHIELD™.

**WARNING:** THIS PRODUCT CANNOT BE ALLOWED TO FREEZE.

**PRECAUTIONS:** Avoid contact with eyes and prolonged contact with skin. Avoid inhaling spray mist. If swallowed can cause irritation, nausea and diarrhea. wear impervious gloves and safety goggles.

**FIRST AID:** Rinse eyes thoroughly for 15 minutes, pulling upper and lower lids apart. Rinse skin thoroughly with running water. If ingested DO NOT CAUSE VOMITING. Drink several glasses of water. Consult a physician. If spray mist is inhaled, remove to fresh air.

**LIMITATION OF LIABILITY:** The user accepts full responsibility and risk in testing this product for the particular application. In no event shall NEW DIMENSIONS SOLUTIONS, LLC be liable for consequential or incidental damages exceeding the cost of this product.

MANUFACTURED BY: New Dimensions Solutions, LLC  
Las Vegas, NV 89169, (800) 731-2231

05/22/07