

SKID SAFE™

Water Based Sealer/Finish

Highly Slip and Stain Resistant
Tough Durable High Gloss - Dries Water Clear

Does Not Require Stripping

Extremely Low Odor

Use On All Flooring Materials

Seals and Protects All Grout Lines

Restores Color of Old Floor Paint

Prevents Rust, Corrosion, Spawling & Crumbling

Guaranteed for 5 years!

VOC Content Only: 19.6 g/l per California Regulations
Safe and Pleasant to Use as Directed
Easy To Apply - Dries In Minutes
Use Indoors & Outdoors
Unique Technology

CAUTION:
MAY BE SKIN AND EYE IRRITANT
Read All Cautions On Side Panel
Before Using This Product
KEEP OUT OF REACH OF CHILDREN!

NET CONTENT:

Quart (0.946 liter) Gallon (3.784 liters) 5 Gallon (18.92 liters)

Stain Resistant To Oil, Gasoline, Food Spills & Uric Acid and More
High Spread Rates Lowers Cost of Use (400-4,000 sq. ft. per gallon)
Does Not Yellow, Peel, Crack, Flake, nor Chip
Allows The Substrate to "Breathe"

May be Applied Over Previously Installed Coatings and Paints In Acceptable Condition
To Avoid The High Cost of Stripping Them

Use On All Masonry, Stone, Vinyl, Metal, Wood, Paint, Composite Materials

Use our SUPER BOND & CLEAN™ for best adhesion on Tile and

CONCRETE BOND & CLEAN™ for best adhesion on Concrete

Do not use on any material which will be either underwater or always wet!

See complete Directions, MSDS, Product Data and more at our web site: www.ndclean.com

APPLICATION DIRECTIONS:

Use SKID SAFE straight from the bottle. Do not shake. Do NOT dilute with water! Pre-clean all flooring materials/paints-new or used- with a NEUTRAL CLEANER (PH of 7) to degrease and remove all residues. Allow porous materials such as limestone, marble, etc. to thoroughly dry out before applying SKID SAFE for about 24 hours. A test application is suggested to insure adequate material preparation, spread rate, appearance, and desired results.

1. Thoroughly clean, and or, strip the material and allow it to be absolutely dry to the touch before applying SKID SAFE. A fan or blower will speed the drying time needed.
 2. Apply a total of 4 coats of SKID SAFE. Allow each coat to dry to the touch.
 3. **On porous materials** such as Concrete, Grout, Paint, Marble, Terrazzo SKID SAFE may be applied with an airless sprayer with a 0.015 or 0.013 tip at 300-500 PSI, or with a hand pump sprayer at about 35 PSI. Use a fine bristled brush for smaller areas. Apply a heavier base coat which deeply penetrates and seals the substrate. The next coats are finely spray misted. Seeing the wetness as the product is applied is sufficient! It is not necessary to over wet an application nor go back and forth with the sprayer!
 4. **On smooth materials** apply with either a pre-rinsed clean dry cotton mop, or with a urethane type sponge mop. Do not use a roller!
 5. After all 4 coats have been applied and the floor is dry, secure the floor from all use for a minimum 8 hours. Then, open for light foot traffic only. Allow floor to CURE for 96 hours-the non water elements get very hard. Bathrooms may be covered with cardboard for 96 hours while curing. Do not drag objects over SKID SAFE to avoid scratches or abrasive damages.
- MAINTENANCE DIRECTIONS:** Clean SKID SAFE with just plain water or a neutral cleaner. A powerwash may be used without ill affect. Do not use disinfectants known to harm plastics.

PRECAUTIONS: Avoid contact with eyes and prolonged contact with skin. Avoid inhaling spray mist. If swallowed can cause irritation, nausea and diarrhea. Wear impervious gloves and safety goggles.

FIRST AID: Rinse eyes thoroughly for 15 minutes, pulling upper and lower lids apart. Rinse skin thoroughly with running water. If ingested DO NOT CAUSE VOMITING. Consult a Physician. If spray mist is inhaled, remove to fresh air.

LIMITATION OF LIABILITY: The user assumes full responsibility and risk in testing this product for the particular application. In no event shall NEW DIMENSIONS SOLUTIONS, LLC be liable for consequential or incidental damages exceeding the cost of this product.

MANUFACTURED BY: New Dimensions Solutions, LLC, Las Vegas, NV 89169
(800) 731-2231, www.ndclean.com Date: 05/22/07